P4BWA

Full size ATX motherboard

User's Manual

Edition: 1.00
2007/10/05



Copyright

Copyright 2007. All rights reserved. This document is copyrighted and all rights are reserved. The information in this document is subject to change without prior notice to make improvements to the products.
This document contains proprietary information and protected by copyright. No part of this document may be reproduced, copied, or translated in any form or any means without prior written permission of the manufacturer.
All trademarks and/or registered trademarks contains in this document are property of their respective owners.

Disclaimer

The company shall not be liable for any incidental or consequential damages resulting from the performance or use of this product.
The company does not issue a warranty of any kind, express or implied, including without limitation implied warranties of merchantability or fitness for a particular purpose.
The company has the right to revise the manual or include changes in the specifications of the product described within it at any time without notice and without obligation to notify any person of such revision or changes.

Trademark

All trademarks are the property of their respective holders.

Any questions please visit our website at http://www.commell.com.tw.

Packing List

Please check package component before you use our products.

Hardware:

P4BWA Full size ATX motherboard x 1

Cable Kit:

Floppy flat cable x 1



DB25 & DB9 cable x 1

Serial ATA ribbon cable x 2



I/O Shield x 1



RAID driver Disk for Windows 2000,

Windows XP and Windows Server 2003

Other Accessories:

Divers CD (including User's Manual) x 1

Index

Chapter1 <Introduction> 6

1.1 <Product Overview> 6

1.2 <Product Specification> 7

1.3 <Component Placement> 9

1.4 <Block Diagram> 10

1.5 <Mechanical Drawing > 11

Chapter 2 <Hardware Setup> 12

2.1 <Connector Location> 12

2.2 <Jumper Location> 13

2.3 <Connector Reference> 14

2.3.1 <Internal Connectors> 14

2.3.2 <External Connectors> 14

2.4 <CPU and Memory Setup> 15

2.4.1 <CPU installation> 15

2.4.2 <Memory installation> 16

2.5 <CMOS Setup> 17

2.6 <Disk on chip interface> 18

2.7 <Serial ATA installation> 19

2.8 <Floppy Installation> 20

2.9 <LAN installation> 21

2.10 <Audio Installation> 22

2.11 <Display Installation> 24

2.12 <USB Installation> 25

2.13 <Power and Fan Installation> 27

2.14 <GPIO & SMBUS interface> 29

2.15 <Serial Port> 30

2.16 <Switch & Indicator> 32

2.17 <Expansion Interface> 33

Chapter 3 <System Configuration> 35

3.1 <SATA configuration> 35

3.2 <SATA RAID Configuration> 36

3.3 <Audio Configuration> 40

3.4 <Video Memory Setup> 41

Chapter 4 <BIOS Setup> 43

Appendix A <I/O Port Pin Assignment> 45

A.1 <Floppy Port> 45

A.2 <Serial Port> 46

A.3 <VGA Port> 46

A.4 <LAN Port> 47

A.5 <SMBus> 47

A.6 <Parallel Port> 48

A.7 <IrDA Port> 48

Appedix B <System Resources> 49

Appedix C <Flash BIOS> 53

C.1 BIOS Auto Flash Tool 53

C.2 Flash Method 53

Appendix D <Programming GPIO's> 54

Appendix E <What Dog timer Setting > 55

Contact Information 56

(This page is left for blank)

Chapter1 <Introduction>

1.1 <Product Overview>

P4BWA is the motherboard with last Intel desktop technology with industrial motherboard form factor. Based on Intel® Q965 and ICH8DO, the board integrates a new Core 2 Quad processor 775-pin socket, DDR2 memory slot, Intel® Graphic Media Accelerator 3000 technology, PCI express interface and Serial ATA II with RAID function for a powerful desktop system.

Intel® LGA775 processor

The Intel® Core 2 Quad processor now comes with a new form factor with 775-pin PLGA package, for 533/800/1066MHz front-side-bus, 4MB L2 cache, and for 65nm manufacturing technology, the PLGA processor without pin header on solder side can make user installing the processor on the socket easier.

Intel® Q965 and ICH8DO chipset

The Intel Q965 integrates DDR2 533/667/800MHz for memory, and Graphic Media Accelerator (GMA) 3000 technology for new graphic engine. It can provide up to 256MB of frame buffer when you install over 512MB of system memory. The ICH8DO integrates with up to 10 USB2.0 interfaces (6 ports for P4BWA) I/O panel, and serial ATA II interface with RAID function.

Dual Intel 82573L Gigabit LAN

Dual Gigabit LAN with Intel 82573L, P4BWA comes with a powerful network function for the system that requires large transfer data of NAS system or Server platform.

PCI-Express interface

P4BWA integrates one x16 and x4 PCI-Express interface, it can provide up to 8GB/s of bandwidth, which AGP 8x can only provide up to 2GB/s.

Multimedia interfaces

P4BWA also integrates 7.1 channel HD audio, Mini-PCI, PCI and ISA interface, for these flexible function, system integrator can built more powerful systems for many applications.

1.2 <Product Specification>

General Specification	
Form Factor	Full size ATX motherboard
CPU	Intel® **Core 2 Quad/Core 2 Duo/Pentium 4/Pentium D/ Celeron D series** processor with **LGA775** socket Package type: PLGA 775 Front side bus: 533/800/1066MT/s (133/200/266/QuadMHz x 4) **Intel® Hyper-Threading Technology and Dual/Quad core** supported, EM64T supported
Memory	4 x 240-pin DDR2 533/667/800MHz SDRAM up to 8GB Unbufferred, none-ECC memory supported only
Chipset	Intel® Q965 (Northbridge) and ICH8DO (Southbridge)
BIOS	Phoenix-Award v6.00PG 8Mb SPI flash BIOS
Green Function	Power saving mode includes doze, standby and suspend modes. ACPI version 1.0 and APM version 1.2 compliant
Watchdog Timer	System reset programmable watchdog timer with 1 ~ 255 sec./min. of timeout value
Real Time Clock	Intel® ICH8DO built-in RTC with lithium battery
Serial ATAII	Intel® ICH8DO integrates 6 Serial ATA II interface RAID 0, 1,5,10 Intel Matrix Storage Technology supported
Multi-I/O Port	
Chipset	Intel® 82801HDO(ICH8DO) with Winbond® W83627DHG and Fintek F81216D controller
Serial Port	Five RS-232 and one RS232/422/485 serial ports
USB Port	Ten Hi-Speed USB 2.0 ports with 480Mbps of transfer rate
Parallel Port	One internal bi-direction parallel port with SPP/ECP/EPP mode
Floppy Port	One internal Floppy port
IrDA Port	One IrDA compliant Infrared interface supports SIR
K/B & Mouse	External PS/2 keyboard and mouse port on rear I/O
GPIO	One 12-pin Digital I/O connector with 8-bit programmable I/O interface
Smart Fan	One CPU fan connector for fan speed controllable
VGA Display Interface	
Chipset	Intel® Q965 GMA3000 (Graphic Memory Controller Hub)
Frame Buffer	Up to 256MB shared with system memory
Connector	External DB15 female connector on rear I/O

Ethernet Interface	
Controller	Two Intel 82573L Gigabit Ethernet controller
Type	Triple speed 10/100/1000Base-T Auto-switching Fast Ethernet Full duplex, IEEE802.3U compliant
Connector	Two External RJ45 connectors with LED on rear I/O
Audio Interface	
Chipset	Intel integrated with Realtek ALC888 HD Audio Intel High Definition Audio compliance
Interface	7.1 channels sound output
Connector	External Audio phone jack for Line-out, Line-in, MIC-in, Surround, Center and Backsurround Onboard front audio connector with pin header Onboard CD-IN and external optical S/PDIF connector
Expansive Interface	
PCI-Express	One x16 PCI-Express slot (***compatible with x1 slot***) One x4 PCI-Express slot (compatible with x 1 slot) Up to 8GB/s of transfer bandwidth Power supply: +3.3V, +12V
PCI	Four-PCI slot (32-bit, 33MHz) Power supply: +3.3V, +5V, +12V, -12V
Mini PCI	One Mini-PCI socket **TYPE III A** (32-bit, 33MHz) Power supply: +3.3V, +5V, 3VSB
ISA	Two ISA slots (without DMA supported)
Power and Environment	
Power Requirement	Standard 24-pin ATX power supply (20-pin is compatible) Standard 8-pin 12v power Input connector (4-pin is compatible)
Dimension	307mm x 244mm (L x W)
Temperature	Operating within 0 ~ 60°C (32 ~ 140°F) Storage within -20 ~ 85°C (-4 ~ 185°F)
Ordering Code	
P4BWA	Support Intel Core 2 Quad LGA775 with DDRII, Onboard VGA, Dual Intel Gigabit LAN 10 x USB2.0, Realtek ALC888 HD Audio, 6 x COM Ports, GPIO, SATA and ISA slot

For further product information please visit the website at http://www.commell.com.tw

1.3 <Component Placement>





1.4 <Block Diagram>



2.4.2 <Memory installation>

P4BWA has four 240-pin DDR2 DIMM support up to 8GB of memory capacity. The memory frequency supports 533/667/800 MHz. Only Non-ECC memory is supported. **Dual-Channel technology** is supported while applying two modules with A+B channel.

DDRII B2
DDRII B1
DDRII A2
DDRII A1





Please check the pin number to match the socket side well before installing memory module.

2.5 <CMOS Setup>

The board's data of CMOS can be setting in BIOS. If the board refuses to boot due to inappropriate CMOS settings, here is how to proceed to clear (reset) the CMOS to its default values.

Jumper: JRTC

Type: Onboard 3-pin jumper

JRTC	Mode
1-2	Clear CMOS
2-3	Normal Operation

Default setting



2.6 <Disk on chip interface>

The board supports 32-pin DiskOnChip 2000. The onboard 32-pin socket, DOC, supports DiskOnChip2000 single chip flash disk in 32-pin DIP JEDEC with jumper selectable address on jumper JDOC.



Jumper: **JDOC**

Type: onboard 3-pin header

JDOC	DiskOnChip Address
1-2	D800h
2-3	D000h

Default setting

2.7 <Serial ATA installation>

P4BWA has six Serial ATA II interfaces with RAID function, the transfer rate of the Serial ATA II can be up to 300MB/s. Please go to http://www.serialata.org/ for more about Serial ATA technology information. Based on Intel® ICH8DO, it supports **Intel® Matrix Storage Technology** with combination of RAID 0,1,5 and 10. The main features of RAID on ICH8DO are listed below:

1. Supports for up to RAID volumes on a single, two-hard drive RAID array.
2. Supports for two, six-hard drive RAID arrays on any of six Serial ATA ports.
3. Supports for Serial ATA ATAPI devices.
4. Supports for RAID spares and automatic rebuild.
5. Supports on RAID arrays, including NCQ and native hot plug.

For more information please visit Intel's official website.

For more about the system setup for Serial ATA, please check the chapter of SATA configuration.



(Associate accessory)

2.8 <Floppy Installation>

P4BWA has one 34-pin floppy interface, it supports use floppy and powering from onboard, please follow up the steps below to install the device.



2.9 <LAN installation>

P4BWA integrates two Gigabit LAN interfaces with Dual Intel 82573L; they provide a standard IEEE 802.3 Ethernet interface for 1000BASE-T, 100BASE-TX and 10BASE-T applications. **P4BWA** provides two RJ45 connectors on the rear I/O panel.



2.10 <Audio Installation>

The board integrates onboard audio interface with REALTEK ALC888 codec, with Intel next generation of audio standard as High Definition Audio, it offers more vivid sound and other advantages than former AC97 audio compliance.

The main specifications of ALC888 are:

- **High-performance DACs with 97dB S/N ratio**
- **10 DAC channels support 16/20/24-bit PCM format for 7.1 audio solution**
- **16/20/24-bit S/PDIF-OUT supports 44.1K/48K/96K/192KHz sample rate**

The board provides 7.1 channels audio phone jacks on rear I/O port, and Line-in/MIC-in ports for front I/O panel through optional cable.



Connector: CN_AUDIO

Type: 10-pin (2 x 5) header (pitch = 2.54mm)

Pin	Description	Pin	Description
1	MIC_L	2	Ground
3	MIC_R	4	ACZ_DET
5	Front_R	6	MIC_JD
7	Sense	8	N/C
9	Front_L	10	Line_JD

Connector: CDIN

Type: 4-pin header (pitch = 2.54mm)

Pin	Description
1	CD – Left
2	Ground
3	Ground
4	CD – Right



2.11 <Display Installation>

P4BWA integrates with Intel® Q965 GMCH for Intel Graphic Media Accelerator (GMA) 3000 technology. It supports Intel® DVMT (Dynamic Video Memory Technology) 3.0 for up to 256MB frame buffer size shared with system memory. With a 400MHz core and DirectX 9 and OpenGL acceleration, **P4BWA** provides the powerful onboard graphics interface without additional graphic card. *(More information please visit Intel's website)*

For more information of configuring the frame buffer size, please check the chapter of video memory configuration.



Intel Q965 GMCH



VGA (DB15)

2.12 <USB Installation>

P4BWA integrates 10 USB2.0 ports. The specifications USB2.0 are listed below:

Interface	USB2.0
Controller	Intel ICH8DO
Transfer Rate	Up to 480Mb/s

The Intel® ICH8DO contains and Enhanced Host Controller Interface (EHCI) and six Universal Host Controller Interfaces (UHCI), it can determine whether your connected device is for USB1.1 or USB2.0, and change the transfer rate automatically.



USB

Connector: **CN_USB1/2**
Type: 10-pin (5 x 2) header for USB1/2 Ports

Pin	Description	Pin	Description
1	VCC	2	VCC
3	Data0-	4	Data1-
5	Data0+	6	Data1+
7	Ground	8	Ground
9	Ground	10	N/C



2.13 <Power and Fan Installation>

The **P4BWA** provides a standard ATX power supply with **24-pin** ATX connector and additional 12V connector, and the board provides one **4-pin** fan connectors supporting smart fan for CPU cooler and two 3-pin cooler fan connectors for system and Northbridge chip. The 8-pin additional power connector is necessary for CPU powering; please connect this well before you finishing the system setup.



Connector: **ATX**
Type: 24-pin ATX power connector

PIN assignment			
1	3.3V	13	3.3V
2	3.3V	14	-12V
3	GND	15	GND
4	5V	16	PS_ON
5	GND	17	GND
6	5V	18	GND
7	GND	19	GND
8	PW_OK	20	-5V
9	5V_SB	21	5V
10	12V	22	5V
11	12V	23	5V
12	3.3V	24	GND

Connector: **CN_12V**
Type: 8-pin standard Pentium 4 additional +12V power connector

Pin	Description	Pin	Description
1	Ground	5	+12V
2	Ground	6	+12V
3	Ground	7	+12V
4	Ground	8	+12V

Connector: **CPUFAN**
Type: 4-pin fan wafer connector

Pin	Description	Pin	Description
1	Ground	2	+12V
3	Fan Speed Detection	4	Sense

Connector: **NBFAN**, **SYSFAN**
Type: 3-pin fan wafer connector

Pin	Description	Pin	Description	Pin	Description
1	Ground	2	+12V	3	Sense

2.14 <GPIO & SMBUS interface>

The board provides a programmable 8-bit digital I/O interface, and one SMBus (System management bus) interface for control panel application.

Connector: **CN_DIO**
Type: onboard 2 x 6-pin header, pitch=2.0mm

Pin	Description	Pin	Description
1	Ground	2	Ground
3	GP10	4	GP14
5	GP11	6	GP15
7	GP12	8	GP16
9	GP13	10	GP17
11	VCC	12	+12V



Connector: **CN_SMBUS**

Type: 5-pin 2.54-pitch header

Pin	Description
1	VCC
2	N/C
3	SMBDATA
4	SMBCLK
5	Ground

2.15 <Serial Port>

The board supports one RS232 serial port and one jumper selectable RS232/422/485 serial ports. The jumper JCSEL1 & JCSEL2 can let you configure the communicating modes for COM2.

Connector: **CN_COM2**

Type: 10-pin (5 x 2) 2.54mm x 2.54mm-pitch box header for COM2



Pin	Description	Pin	Description
1	DCD/422RX-/485-	2	RXD/422RX+/485+
3	TXD/422TX+	4	DTR/422TX-
5	GND	6	DSR
7	RTS	8	CTS
9	RI	10	N/C



	JCSEL1	JCSEL2
SIR		
RS-422		
RS-485		
RS-232		



2.16 <Switch & Indicator>

The **JFRNT** provides front control panel of the board, such as power button, reset and beeper, etc. Please check well before you connecting the cables on the chassis.

Connector: **JFRNT**
Type: onboard 14-pin (2 x 7) 2.54-pitch header

Function	Signal	PIN		Signal	Function
IDE LED	HDLED+	1	2	PWDLED+	Power LED
	HDLED-	3	4	N/C	
Reset	Reset+	5	6	PWDLED-	
	Reset-	7	8	SPKIN+	Speaker
	N/C	9	10	N/C	
Power Button	PWRBT+	11	12	N/C	
	PWRBT-	13	14	SPKIN-	



2.17 <Expansion Interface>

P4BWA has one x16 and x4 PCI-Express slot. PCI-Express is the last expansion interface technology, for its serial data transfer scheme, each lane will be up to 500MB/s (duplex), and the x16 (16 lanes) can be up to 8GB/s more than 2GB/s as AGP 8x bus transfer rate. The x4 slot can be also for x1 compatible use.



(This page is left for blank)

Chapter 3 <System Configuration>

3.1 <SATA configuration>

SATA Mode:



This option can let you select whether the Serial ATA hard drives would work under normal IDE mode or RAID mode. The RAID mode need more than one HDD is applied.

3.2 <SATA RAID Configuration>

The board integrates Intel® ICH8DO with RAID function for Serial ATA II drives, and supports the configurations below:

RAID 0 (Stripping): Two hard drives operating as one drive for optimized data R/W performance. It needs two unused drives to build this operation.

RAID 1 (Mirroring): Copies the data from first drive to second drive for data security, and if one drive fails, the system would access the applications to the workable drive. It needs two unused drives or one used and one unused drive to build this operation. The second drive must be the same or lager size than first one.

RAID 5 (striping with parity)

A RAID 5 array contains three or more hard drives where the data is divided into manageable blocks called strips. Parity is a mathematical method for recreating data that was lost from a single drive, which increases fault-tolerance. The data and parity are striped across all the hard drives in the array. The parity is striped in a rotating sequence to reduce bottlenecks associated with the parity calculations.

RAID 10 (RAID 0+1)

A RAID 10 array uses four hard drives to create a combination of RAID levels 0 and 1. The data is striped across a two-drive array forming the RAID 0 component. Each of the drives in the RAID 0 array is then mirrored by a RAID 1 component.

Intel Matrix Storage Technology: This technology would allow you to use **RAID 0+1** mode on only two drives (4 drives needed on traditional RAID 0+1). It will create two partitions on each hard drive to simulate **RAID 0** and **RAID 1**. It also can let you modify the partition size without re-formatted.

For more information of Intel Matrix Storage Technology, please visit Intel's website.

If you need to install an operation system on the RAID set, please use the driver disk attached in the package when it informs you to obtain the RAID drivers.


Intel(R) Application Accelerator RAID Option ROM v4.0.0.6211
Copyright(C) 2003-04 Intel Corporation. All Rights Reserved.
[MAIN MENU]
1. Create RAID Volume
2. Delete RAID Volume
3. Reset Disks to Non-RAID
4. Exit
[DISK/VOLUME INFORMATION]
RAID Volumes:
None defined.
Non-RAID Disks:
Port Drive Model Serial # Size Type/Status (Vol ID)
xxxxxxxx 74.5GB Non-RAID Disk
xxxxxxxx 74.5GB Non-RAID Disk
[↓↑] -Select [ESC] Exit [Enter] -Select Menu

Please press **<CTRL+I>** to enter the RAID configuration menu.

You can setup the RAID under operation system for Microsoft® Windows XP SP1 or Windows 2000 SP4 version, please install the Intel® Application Accelerator Ver.4.5 later to support RAID configuration with Intel® Matrix Storage Technology.

1. After installing Intel Application Accelerator, please execute Intel® Storage Utility.


Intel(R) Storage Utility
File View Actions Help
Create RAID Volume
Create RAID Volume from Existing Hard Drive
intel
Intel RAID Controllers
Intel(R) 82801FR SATA RAID Cont
Non-RAID Hard Drives
HDS722525VLSA80
HDS722525VLSA80
Information
This item displays any storage controller(s) in the system currently managed by the Intel Storage Utility.
Demo configuration for 2 SATA Drives and set as Intel Matrix Storage Technology set

2. Select Actions to Create RAID Volume


Rename the Volume name
Select RAID Level as 0
Left as default
Create RAID Volume Wizard
Configure Volume
You can configure the new RAID volume by entering a name and by selecting the RAID level and strip size below.
Volume Name
RAID_Volume0
The name is limited to 16 English alpha-numeric characters.
RAID Level
RAID 0
Strip Size
128 KB
< Back
Next >
Cancel

3. Please select two hard drives to prepare to set the RAID volume


Create RAID Volume Wizard
Select Volume Location
Specify the location for the new RAID volume by selecting 2 hard drives or an array below.
Available
Port 0: HDS722525VLSA80 - SerialA
Port 3: HDS722525VLSA80 - SerialA
Selected
WARNING: Selecting hard drives will permanently delete the data on the hard drives. Back up all important data before continuing.
Selecting an existing array will preserve any volume(s) on the array.
< Back
Next >
Cancel

4. Specify the Volume size

Tune this bar to specify the volume size, if you specify the volume size lower than maximum, you can create a second volume for another RAID set.
(Make RAID 0+1 on only two hard drives)


Create RAID Volume Wizard
Specify Volume Size
Use the fields or the slider below to specify the amount of available array space to be used by the new RAID volume.
Maximum Volume Size (GB): 465.8
Minimum Volume Size (GB): 0
Percentage of Available Space: 50
Volume Size (GB): 232.9
If you specify a size that is lower than the maximum volume size, you will need to create a second RAID volume in order to utilize the remaining space.
< Back
Next >
Cancel



5. Repeat the step 1 to create second volume as RAID Level 1.

For other configuration set please click Help on tool bar.

3.3 <Audio Configuration>

The board integrates Intel® ICH8DO with REALTEK® ALC888codec. It can support 7.1channel sound under system configuration. Please follow the steps below to setup your sound system.

1. Install REALTEK AC97 Audio driver.

2. Lunch the control panel and Sound Effect Manager.

3. Select Speaker Configuration

4. Select the sound mode to meet your speaker system.

3.4 <Video Memory Setup>

Based on Intel® Q965 chipset with GMA (Graphic Media Accelerator) 3000, the board supports Intel® DVMT (Dynamic Video Memory Technology) 3.0, which would allow the video memory be triggered up to 256MB.

To support DVMT, you need to install the Intel GMA 3000 Driver with supported OS.

BIOS Setup:


Phoenix - AwardBIOS CMOS Setup Utility
Advanced Chipset Features
DRAM RAS# to CAS# Delay [Auto]
DRAM RAS# Precharge [Auto]
Precharge dealy (tRAS) [Auto]
System Memory Frequency [Auto]
SLP_S4# Assertion Width [4 to 5 Sec.]
System BIOS Cacheable [Enabled]
Video BIOS Cacheable [Disabled]
Memory Hole At 15M-16M [Disabled]
PCI Express Root Port Func [Press Enter]
** VGA Setting **
PEG/Onchip VGA Control [Auto]
PEG Force X1 [Disabled]
On-Chip Video Memory Size [Press Enter]
On-Chip Frame Buffer Size [8MB]
FIXED Memory Size [24MB]
DVMT Memory Size [63MB]
Boot Display [Auto]
Item Help
Menu Level
↑↓→←:Move Enter:Select +/-/PU/PD:Value F10:Save ESC:Exit F1:General Help
F5: Previous Values F6: Fail-Safe Defaults F7: Optimized Defaults

On-Chip Video Memory Size: This option combines three items below for setup.

On-Chip Frame Buffer Size:

This item can let you select video memory which been allocated for legacy VGA and SVGA graphics support and compatibility. The available option is **1MB** and **8MB**.

Fixed Memory Size:

This item can let you select a static amount of page-locked graphics memory which will be allocated during driver initialization. Once you select the memory amount, it will be no longer available for system memory.

DVMT Memory Size:

This item can let you select a maximum size of dynamic amount usage of video memory, the system would configure the video memory depends on your application, this item is

strongly recommend to be selected as **MAX DVMT**.

Fixed + DVMT Memory Size:

You can select the fixed amount and the DVMT amount at the same time for a guaranteed video memory and additional dynamic video memory, please check the table below for available setting.

System Memory	On-Chip Frame Buffer Size	Fixed Memory Size	DVMT Memory Size	Total Graphic Memory
256MB ~ 511MB	1MB	128MB	0MB	128MB
	1MB	0MB	128MB	128MB
	8MB	128MB	0MB	128MB
	8MB	0	128MB	128MB
512MB~1023MB	1MB	128MB	0	128MB
	1MB	256MB	0	256MB
	1MB	0	128MB	128MB
	1MB	0	256MB	256MB
	8MB	128MB	0	128MB
	8MB	256MB	0	256MB
	8MB	0	128MB	128MB
	8MB	0	256MB	256MB

Notice:

1. The On-Chip Frame Buffer Size would be included in the Fixed Memory.

Please select the memory size according to this table

Chapter 4 <BIOS Setup>

The motherboard uses the Award BIOS for the system configuration. The Award BIOS in the single board computer is a customized version of the industrial standard BIOS for IBM PC AT-compatible computers. It supports Intel x86 and compatible CPU architecture based processors and computers. The BIOS provides critical low-level support for the system central processing, memory and I/O sub-systems.

The BIOS setup program of the single board computer let the customers modify the basic configuration setting. The settings are stored in a dedicated battery-backed memory, NVRAM, retains the information when the power is turned off. If the battery runs out of the power, then the settings of BIOS will come back to the default setting.

The BIOS section of the manual is subject to change without notice and is provided here for reference purpose only. The settings and configurations of the BIOS are current at the time of print, and therefore they may not be exactly the same as that displayed on your screen.

To activate CMOS Setup program, press ＜DEL＞ key immediately after you turn on the system. The following message "Press DEL to enter SETUP" should appear in the lower left hand corner of your screen. When you enter the CMOS Setup Utility, the Main Menu will be displayed as **Figure 4-1**. You can use arrow keys to select your function, press ＜Enter＞ key to accept the selection and enter the sub-menu.

Figure 4-1 CMOS Setup Utility Main Screen

(This page is left for blank)

Appendix A <I/O Port Pin Assignment>

A.1 <Floppy Port>

Connector: **FDD**

Type: 34-pin (2 x 17) 2.54-pitch box header



Pin	Description	Pin	Description
1	Ground	2	DRIVE DENSITY SELECT 0
3	Ground	4	DRIVE DENSITY SELECT 1
5	Ground	6	N/C
7	Ground	8	INDEX-
9	Ground	10	MOTOR ENABLE A-
11	Ground	12	DRIVER SELECT B-
13	Ground	14	DRIVER SELECT A-
15	Ground	16	MOTOR ENABLE B-
17	Ground	18	DIRECTION-
19	Ground	20	STEP-
21	Ground	22	WRITE DATA-
23	Ground	24	WRITE GATE-
25	Ground	26	TRACK 0-
27	Ground	28	WRITE PROTECT-
29	Ground	30	READ DATA-
31	Ground	32	HEAD SELECT-
33	Ground	34	DISK CHANGE-

A.2 <Serial Port>



Connector: **COM1**
Type: 9-pin D-sub male connector on I/O Panel

Pin	Description	Pin	Description
1	DCD	6	DSR
2	SIN	7	RTS
3	SO	8	CTS
4	DTR	9	RI
5	Ground		



Connector: **COM2/3/4/5/6**
Type: 10-pin (2x5) 2.54-pitch box header

Pin	Description	Pin	Description
1	DCD-	6	DSR-
2	SIN-	7	RTS-
3	SO-	8	CTS-
4	DTR-	9	RI
5	Ground	10	N/C

A.3 <VGA Port>



Connector: **VGA**
Type: 15-pin D-sub female connector on I/O Panel

Pin	Description	Pin	Description	Pin	Description
1	RED	6	Ground	11	N/C
2	GREEN	7	Ground	12	5VCDA
3	BLUE	8	Ground	13	HSYNC
4	N/C	9	LVGA5V	14	VSYNC
5	Ground	10	Ground	15	5VCLK

A.4 <LAN Port>



Connector: **RJ45**
Type: RJ45 connector with LED on I/O Panel

Pin	1	2	3	4	5
Description	TRD0+	TRD0-	TRD1+	TRD1-	NC

Pin	6	7	8	9	10
Description	NC	TRD2+	TRD2-	TRD3+	TRD3-

A.5 <SMBus>

Connector: **CN_SMBUS**
Type: 5-pin SMBus (1x5)2.54 pitch header

Pin	Description	Pin	Description
1	VCC	2	N/C
3	SMBDATA	4	SMBCLK
5	Ground		



A.6 <Parallel Port>

Connector: **LPT (PRINTER)**
Type: 26-pin (2 x 13) 2.54-pitch box header



Pin	Description	Pin	Description
1	STROBE-	14	AUTO FEED-
2	D0	15	ERROR-
3	D1	16	INITIALIZE-
4	D2	17	SELECT INPUT-
5	D3	18	Ground
6	D4	19	Ground
7	D5	20	Ground
8	D6	21	Ground
9	D7	22	Ground
10	ACKNOWLEDGE-	23	Ground
11	BUSY	24	Ground
12	PAPER EMPTY	25	Ground
13	SELECT+	26	N/C

A.7 <IrDA Port>

Connector: **CN_IR**
Type: 5-pin header for SIR Port

Pin	Description
1	Vcc
2	N/C
3	IRRX
4	Ground
5	IRTX

Appedix B <System Resources>

B1. <I/O Port Address Map>

[00000000 - 0000000F] Direct memory access controller
[00000000 - 00000CF7] PCI bus
[00000010 - 0000001F] Motherboard resources
[00000020 - 00000021] Programmable interrupt controller
[00000022 - 0000003F] Motherboard resources
[00000040 - 00000043] System timer
[00000044 - 0000005F] Motherboard resources
[00000060 - 00000060] Standard 101/102-Key or Microsoft Natural PS/2 Keyboard
[00000061 - 00000061] System speaker
[00000062 - 00000063] Motherboard resources
[00000064 - 00000064] Standard 101/102-Key or Microsoft Natural PS/2 Keyboard
[00000065 - 0000006F] Motherboard resources
[00000070 - 00000073] System CMOS/real time clock
[00000074 - 0000007F] Motherboard resources
[00000080 - 00000090] Direct memory access controller
[00000091 - 00000093] Motherboard resources
[00000094 - 0000009F] Direct memory access controller
[000000A0 - 000000A1] Programmable interrupt controller
[000000A2 - 000000BF] Motherboard resources
[000000C0 - 000000DF] Direct memory access controller
[000000E0 - 000000EF] Motherboard resources
[000000F0 - 000000FF] Numeric data processor
[00000274 - 00000277] ISAPNP Read Data Port
[00000279 - 00000279] ISAPNP Read Data Port
[000002F8 - 000002FF] Communications Port (COM2)
[00000378 - 0000037F] Printer Port (LPT1)
[000003B0 - 000003BB] Intel(R) Q965/Q963 Express Chipset Family
[000003C0 - 000003DF] Intel(R) Q965/Q963 Express Chipset Family
[000003E8 - 000003EF] Communications Port (COM3)
[000003F0 - 000003F5] Standard floppy disk controller
[000003F7 - 000003F7] Standard floppy disk controller
[000003F8 - 000003FF] Communications Port (COM1)
[00000400 - 000004BF] Motherboard resources
[00000880 - 0000088F] Motherboard resources

[00000A79 - 00000A79] ISAPNP Read Data Port
[00000D00 - 0000FFFF] PCI bus
[00009000 - 00009FFF] Intel(R) ICH8 Family PCI Express Root Port 1 - 283F
[0000A000 - 0000AFFF] Intel(R) Q963/Q965 PCI Express Root Port - 2991
[0000B000 - 0000BFFF] Intel(R) ICH8 Family PCI Express Root Port 6 - 2849
[0000BF00 - 0000BF1F] Intel(R) PRO/1000 PL Network Connection
[0000D000 - 0000DFFF] Intel(R) ICH8 Family PCI Express Root Port 5 - 2847
[0000DF00 - 0000DF1F] Intel(R) PRO/1000 PL Network Connection #2
[0000ED00 - 0000ED0F] Intel(R) ICH8 2 port Serial ATA Storage Controller - 2825
[0000EE00 - 0000EE0F] Intel(R) ICH8 2 port Serial ATA Storage Controller - 2825
[0000EF00 - 0000EF03] Intel(R) ICH8 2 port Serial ATA Storage Controller - 2825
[0000F000 - 0000F007] Intel(R) ICH8 2 port Serial ATA Storage Controller - 2825
[0000F100 - 0000F103] Intel(R) ICH8 2 port Serial ATA Storage Controller - 2825
[0000F200 - 0000F207] Intel(R) ICH8 2 port Serial ATA Storage Controller - 2825
[0000F400 - 0000F40F] Intel(R) ICH8 4 port Serial ATA Storage Controller - 2820
[0000F500 - 0000F50F] Intel(R) ICH8 4 port Serial ATA Storage Controller - 2820
[0000F600 - 0000F603] Intel(R) ICH8 4 port Serial ATA Storage Controller - 2820
[0000F700 - 0000F707] Intel(R) ICH8 4 port Serial ATA Storage Controller - 2820
[0000F800 - 0000F803] Intel(R) ICH8 4 port Serial ATA Storage Controller - 2820
[0000F900 - 0000F907] Intel(R) ICH8 4 port Serial ATA Storage Controller - 2820
[0000FA00 - 0000FA1F] Intel(R) ICH8 Family USB Universal Host Controller - 2832
[0000FB00 - 0000FB1F] Intel(R) ICH8 Family USB Universal Host Controller - 2831
[0000FC00 - 0000FC1F] Intel(R) ICH8 Family USB Universal Host Controller - 2830
[0000FD00 - 0000FD1F] Intel(R) ICH8 Family USB Universal Host Controller - 2835
[0000FE00 - 0000FE1F] Intel(R) ICH8 Family USB Universal Host Controller - 2834
[0000FF00 - 0000FF07] Intel(R) Q965/Q963 Express Chipset Family
[0000FFFF - 00010006] Communications Port (COM4)
[0000FFFF - 00010006] Communications Port (COM5)
[0000FFFF - 00010006] Communications Port (COM6)

B2. <Memory Address Map>

[00000000 - 0009FFFF] System board
[000A0000 - 000BFFFF] Intel(R) Q965/Q963 Express Chipset Family
[000A0000 - 000BFFFF] PCI bus
[000C0000 - 000DFFFF] PCI bus
[000E0000 - 000EFFFF] System board
[000F0000 - 000FFFFF] System board
[00100000 - CF6DFFFF] System board
[CF6E0000 - CF6FFFFF] System board
[CF700000 - CF7FFFFF] System board
[CF750000 - FEBFFFFF] PCI bus
[D0000000 - DFFFFFFF] Intel(R) Q965/Q963 Express Chipset Family
[E0000000 - EFFFFFFF] Motherboard resources
[FD400000 - FD4FFFFF] Intel(R) Q963/Q965 PCI Express Root Port - 2991
[FD500000 - FD5FFFFF] Intel(R) Q963/Q965 PCI Express Root Port - 2991
[FD800000 - FD8FFFFF] Intel(R) Q965/Q963 Express Chipset Family
[FD900000 - FD9FFFFF] Intel(R) ICH8 Family PCI Express Root Port 6 - 2849
[FDA00000 - FDAFFFFF] Intel(R) ICH8 Family PCI Express Root Port 6 - 2849
[FDAE0000 - FDAFFFFF] Intel(R) PRO/1000 PL Network Connection
[FDB00000 - FDBFFFFF] Intel(R) ICH8 Family PCI Express Root Port 5 - 2847
[FDC00000 - FDCFFFFF] Intel(R) ICH8 Family PCI Express Root Port 5 - 2847
[FDCE0000 - FDCFFFFF] Intel(R) PRO/1000 PL Network Connection #2
[FDD00000 - FDDFFFFF] Intel(R) ICH8 Family PCI Express Root Port 1 - 283F
[FDE00000 - FDEFFFFF] Intel(R) ICH8 Family PCI Express Root Port 1 - 283F
[FDFF8000 - FDFFBFFF] Microsoft UAA Bus Driver for High Definition Audio
[FDFFD000 - FDFFD0FF] Intel(R) ICH8 Family SMBus Controller - 283E
[FDFFE000 - FDFFE3FF] Intel(R) ICH8 Family USB2 Enhanced Host Controller - 2836
[FDFFF000 - FDFFF3FF] Intel(R) ICH8 Family USB2 Enhanced Host Controller - 283A
[FEC00000 - FEC00FFF] System board
[FED13000 - FED1FFFF] System board
[FED20000 - FED9FFFF] System board
[FEE00000 - FEE00FFF] System board
[FFB00000 - FFB7FFFF] System board
[FFB80000 - FFBFFFFF] Intel(R) 82802 Firmware Hub Device
[FFF00000 - FFFFFFFF] System board

B3. <System IRQ Resources>

IRQ :

(ISA) 0 System timer
(ISA) 1 Standard 101/102-Key or Microsoft Natural PS/2 Keyboard
(ISA) 3 Communications Port (COM2)
(ISA) 4 Communications Port (COM1)
(ISA) 5 Communications Port (COM3)
(ISA) 6 Standard floppy disk controller
(ISA) 8 System CMOS/real time clock
(ISA) 9 Microsoft ACPI-Compliant System
(ISA) 12 PS/2 Compatible Mouse
(ISA) 13 Numeric data processor
(PCI) 15 Intel(R) ICH8 Family SMBus Controller - 283E
(PCI) 16 Intel(R) Q965/Q963 Express Chipset Family
(PCI) 16 Intel(R) ICH8 Family PCI Express Root Port 1 - 283F
(PCI) 16 Intel(R) ICH8 Family PCI Express Root Port 5 - 2847
(PCI) 16 Intel(R) ICH8 Family USB Universal Host Controller - 2834
(PCI) 16 Intel(R) PRO/1000 PL Network Connection #2
(PCI) 16 Intel(R) Q963/Q965 PCI Express Root Port - 2991
(PCI) 17 Intel(R) ICH8 Family PCI Express Root Port 6 - 2849
(PCI) 17 Intel(R) PRO/1000 PL Network Connection
(PCI) 18 Intel(R) ICH8 Family USB Universal Host Controller - 2832
(PCI) 18 Intel(R) ICH8 Family USB2 Enhanced Host Controller - 283A
(PCI) 19 Intel(R) ICH8 2 port Serial ATA Storage Controller - 2825
(PCI) 19 Intel(R) ICH8 4 port Serial ATA Storage Controller - 2820
(PCI) 19 Intel(R) ICH8 Family USB Universal Host Controller - 2831
(PCI) 21 Intel(R) ICH8 Family USB Universal Host Controller - 2835
(PCI) 22 Microsoft UAA Bus Driver for High Definition Audio
(PCI) 23 Intel(R) ICH8 Family USB Universal Host Controller - 2830
(PCI) 23 Intel(R) ICH8 Family USB2 Enhanced Host Controller - 2836

Appedix C <Flash BIOS>

C.1 BIOS Auto Flash Tool

The board is based on Award BIOS and can be updated easily by the BIOS auto flash tool. You can download the tool online at the address below:

http://www.award.com
http://www.commell.com.tw/support/support.htm

File name of the tool is "awdflash.exe", it's the utility that can write the data into the BIOS flash ship and update the BIOS.

C.2 Flash Method

1. Please make a bootable floppy disk.
2. Get the last .bin files you want to update and copy it into the disk.
3. Copy awardflash.exe to the disk.
4. Power on the system and flash the BIOS. (Example: C:/ awardflash XXX.bin)
5. Re-star the system.

Any question about the BIOS re-flash please contact your distributors or visit the web-site at below:

http://www.commell.com.tw/support/support.htm

Appendix D <Programming GPIO's>

The GPIO can be programmed with the MSDOS debug program using simple IN/OUT commands.The following lines show an example how to do this.

GPIO0…..GPIO7 bit0……bit7

-o 4E 87 ;enter configuration

-o 4E 87

-o 4E 07

-o 4F 09 ;enale GPIO function

-o 4E 30

-o 4F 02 ;enable GPIO configuration

-o 4E F0

-o 4F xx ;set GPIO as input/output; set '1' for input,'0'for output

-o 4E F1

-o 4F xx ;if set GPIO's as output,in this register its value can be set

Optional :

-o 4E F2

-o 4F xx ; Data inversion register ; '1' inverts the current valus of the bits ,'0' leaves them as they are

-o 4E 30

-o 4F 01 ; active GPIO's

For further information, please refer to Winbond W83627DHG datasheet.

Appendix E <What Dog timer Setting >

The watchdog timer makes the system auto-reset while it stops to work for a period. The integrated watchdog timer can be setup as system reset mode by program.

Timeout Value Range

- 1 to 255
- Second or Minute

Program Sample

Watchdog timer setup as system reset with 5 second of timeout

-O 4E, 87	
-O 4E, 87	
-O 4E, 07	
-O 4F, 08	Logical Device 8
-O 4E, 30	Activate
-O 4F, 01	
-O 4E, F5	Set as Second*
-O 4F, 00	
-O 4E, F6	Set as 5
-O 4F, 05	

* Minute: bit 3 = 0; Second: bit 3 = 1

You can select Timer setting in the BIOS, after setting the time options, the system will reset according to the period of your selection.


Phoenix - AwardBIOS CMOS Setup Utility
Integrated Peripherals
OnChip IDE Device [Press Enter]
Onboard Device [Press Enter]
SuperIO Device [Press Enter]
Watch Dog Timer Select [Disabled]
Item Help
Menu Level ▶
Watch Dog Timer Select
Disabled ..... [▮]
10 Sec ..... [ ]
20 Sec ..... [ ]
30 Sec ..... [ ]
40 Sec ..... [ ]
1 Min ..... [ ]
2 Min ..... [ ]
4 Min ..... [ ]
↑↓:Move ENTER:Accept ESC:Abort
↑↓→←:Move Enter:Select +/-/PU/PD:Value F10:Save ESC:Exit F1:General Help
F5: Previous Values F6: Fail-Safe Defaults F7: Optimized Defaults

Contact Information

Any advice or comment about our products and service, or anything we can help you please don't hesitate to contact with us. We will do our best to support you for your products, projects and business.

Taiwan Commate Computer Inc.

Address	8F, No. 94, Sec. 1, Shin Tai Wu Rd., Shi Chih Taipei Hsien, Taiwan
TEL	+886-2-26963909
FAX	+886-2-26963911
Website	http://www.commell.com.tw
E-Mail	info@commell.com.tw (General Information) tech@commell.com.tw (Technical Support)

Commell is our trademark of industrial PC division

COMMELL
Stage For Your Success